

EASYLIFTER

for easy lifting of manhole covers

↑ EASYLIFTER

PRODUCT DESCRIPTION

- We recommend using the EasyLifter for fillable access covers as of a weight of 50 kg.
- Our EasyLifters are designed for a load of up to 300 kg/EasyLifter. Thus, an easy opening and moving of access covers of up to 600 kg is enabled.
- The lifting height of the EasyLifter is 180 mm.
- Our EasyLifters are delivered including the FF universal bolts with alternatively M10 or M12 threads.
- For the protection of the floor finish of the access cover, a plastic coating is applied to the bottom side of the lifting gear.
- The wheels are equipped with a thermoplastic rubber coating and protect your flooring.
- A trapezoidal thread spindle enables a quick and easy opening of the access cover.

USE

1. Remove the FF universal bolts from the cover
2. Position both EasyLifters diagonally opposite of each other (see pic. 2)
3. Insert the FF universal bolts through the opening of the EasyLifter into the cover and hand-tighten them (see pic. 3)
4. Use the special crack handle to lift the cover until it is just above the ground
5. Now, slowly roll the cover to the side (see pic. 4+5)



Watch
application
video

PARTICULAR ADVANTAGES

- Lifting and moving the manhole cover in a way simple and fast
- Opening and moving manhole covers up to 600 kg
- Universal bolts M10-M12 included
- Recommended for manhole covers weighing more than 50 kg