
ROUND FLOOR ACCESS COVER IN STAINLESS STEEL



SA4 - weatherproof, with power-assisted opening, shatterproof










FRAMES

Type ES1: made with a stainless steel profile equipped with pre-drilled fins, including dowels for direct installation on concrete

Type ES 3: alternatively with zanches to be fixed during the appropriate throwing of the support base



APPLICATION FIELDS

Ducts of all types, for example:

- · Fountain and spring wells
- Water interception wells
- · Wells for settling tanks
- · Rainwater recovery wells

EXECUTION MODELS

- Type RA: without insulation
- Type RB: with insulation
- Type RC: with air vent, wihout insulation
- Type RD: with air vent, with insulation

MANHOLE COVER

Solid cover made from 4 mm thick stainless steel, with assisted opening and internal locking device to prevent closing accidental. Equipped with hydraulic pistons that facilitate its opening and from sturdy hidden hinges. Opening the lid up to 100° and self-tightening closure with oval brass cap.

GASKET

Equipped with a replaceable and resistant perimeter gasket atmospheric agents.

ITEM		Material	Nominal size	Light hole [ca. mm]	Overall frame size [ca. mm]	M - S
Type RA	SA4-600RA	1.4301/1.4571	620	620	700	S
	SA4-800RA	1.4301/1.4571	800	800	880	S
	SA4-1000RA	1.4301/1.4571	1000	1000	1080	S
	SA4-1200RA	1.4301/1.4571	1200	1200	1280	S
Type RB	SA4-600RB	1.4301/1.4571	620	620	700	S
	SA4-800RB	1.4301/1.4571	800	800	880	S
	SA4-1000RB	1.4301/1.4571	1000	1000	1080	S
	SA4-1200RB	1.4301/1.4571	1200	1200	1280	S
Type RC	SA4-600RC	1.4301/1.4571	620	620	700	S
	SA4-800RC	1.4301/1.4571	800	800	880	S
	SA4-1000RC	1.4301/1.4571	1000	1000	1080	S
	SA4-1200RC	1.4301/1.4571	1200	1200	1280	S
Type RD	SA4-600RD	1.4301/1.4571	620	620	700	S
	SA4-800RD	1.4301/1.4571	800	800	880	S
	SA4-1000RD	1.4301/1.4571	1000	1000	1080	S
	SA4-1200RD	1.4301/1.4571	1200	1200	1280	S

Special size on enquiry!

M Available in stock while supplies last

S Customized production



